

SouthWest Civil War Association

Artillery Safety Test  
(2008)

1.) The minimum Battlefield Side Safety Zone between a loaded artillery piece and any other non-crew person is:

- A.) 5 yards
- B.) 10 yards
- C.) 15 yards
- D.) 20 yards

2.) The minimum Battlefield Safety Zone between an open pass box or limber and any other non-crew member is:

- A.) 5 yards
- B.) 10 yards
- C.) 15 yards
- D.) 20 yards

3.) The minimum Battlefield Safety Zone between the front of a loaded artillery piece is:

- A.) 5 yards
- B.) 10 yards
- C.) 15 yards
- D.) 20 yards

**4.) Implements placed vertically on the hubs or wheels of artillery piece wheels indicate that:**

- A.) The gun is loaded
- B.) The gun is empty
- C.) The gun has misfired

**5.) Implements held over the artillery piece in an "X" indicate:**

- A.) The gun is loaded
- B.) The gun is empty
- C.) The gun has misfired

**6.) The minimum Battlefield Safety Zone in front of an artillery piece that has misfired is:**

- A.) 5 yards
- B.) 10 yards
- C.) 15 yards
- D.) 20 yards

**7.) Immediately prior to the command "Fire", the Chief of the Piece will call:**

- A.) "Ready" and/or "Clear Front"
- B.) "On Your Mark"
- C.) No preparatory command is given

**THANK YOU FOR TAKING THIS TEST. BE CAREFUL AND SAFE!**

You need at least 80% correct to pass Pass\_\_\_\_\_ Fail \_\_\_\_\_ (6 of 7)

Unit Commander's Signature: \_\_\_\_\_ Date: \_\_\_\_\_

Unit Commander's Name: \_\_\_\_\_

For administrative use only

Received: \_\_/\_\_/\_\_ Logged: \_\_/\_\_/\_\_ Filed: \_\_/\_\_/\_\_